


- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTONICS The Shape of Light			<p>Plastic Moulding General Tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing.</p>	<p>DO NOT SCALE DRAWING</p>		<p>FIRST ANGLE PROJECTION</p> 	
				BEACON OPTONICS			
	NAME	SIGNATURE	DATE	<p>Family</p> Glitter Series			
DRAWN	Ankur Sharma	Ankur Sharma	15.02.2023				
CHK'D	Anuj Sharma	Anuj Sharma	15.02.2023				
APPV'D	Pradyumna Shandilya	Pradyumna	15.02.2023				
MATERIAL:	Polycarbonate(Makrolon 2407,Teijin 1225Z)			<p>PRT NO.</p> BO01-Glitter-2x2-5050-60°			
<p>1:-All Dimensions are in mm</p> <p>2:-Open Tolerance is +/- 0.2</p>	<p>This drawing is the property of Beacon Optonics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optonics.</p>			<p>DWG NO.</p> BO01		A4	
						REVISION	
	WEIGHT: 7.0Gm			SCALE:1:1		SHEET 1 OF 1	

<div></div> <div>BEACON OPTONICS The Shape of Light</div>			Plastic Moulding General Tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing.	
	NAME	SIGNATURE	DATE	
DRAWN	Ankur Sharma	Ankur Sharma	15.02.2023	
CHK'D	Anuj Sharma	Anuj Sharma	15.02.2023	
APPV'D	Pradyumna Shandilya	Pradyumna	15.02.2023	
MATERIAL:	Polycarbonate(Makrolon 2407,Teijin 1225Z)			
1:-All Dimensions are in mm	This drawing is the property of Beacon Optonics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optonics.			
2:-Open Tolerance is +/- 0.2				
WEIGHT: 7.0Gm				

Plastic Moulding General Tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing.