



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTONICS</div> <div>The Shape of Light</div>			<div>Plastic Moulding General Tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing.</div>	<div>DO NOT SCALE DRAWING</div>		<div>FIRST ANGLE PROJECTION</div> <div></div>	
				<div>BEACON OPTONICS</div>			
	NAME	SIGNATURE	DATE	<div>Family</div> <div>Glitter Series</div> <div>PRT NO.</div> <div>BO02-Glitter-2x2-5050-90°</div>			
DRAWN	Ankur Sharma	Ankur Sharma	15.02.2023				
CHK'D	Anuj Sharma	Anuj Sharma	15.02.2023				
APPV'D	Pradyumna Shandilya	Pradyumna	15.02.2023				
MATERIAL:	Polycarbonate(Makrolon 2407,Teljin 1225Z)			<div>DWG NO.</div> <div>BO02</div>			A4
<div>1:-All Dimensions are in mm</div> <div>2:-Open Tolerance is +/- 0.2</div>	<div>This drawing is the property of Beacon Optonics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optonics.</div>						REVISION
				WEIGHT: 7.0Gm			SCALE:1:1