



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTONICS The Shape of Light			Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L			DO NOT SCALE DRAWING		FIRST ANGLE PROJECTION 	
						BEACON OPTONICS			
	NAME	SIGNATURE	DATE	Family					
DRAWN	Ankur Sharma	Ankur Sharma	21.02.2023	Glisten Series					
CHK'D	Anuj Sharma	Anuj Sharma	21.02.2023						
APP'V'D	Pradyumna Shandilya	Pradyumna	21.02.2023						
MATERIAL:	Polycarbonate(Makrolon 2407,Teljin 1225Z)			PRT NO. BO06-Glisten-3x3-5050-90°					
1-All Dimensions are in mm 2-Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optonics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optonics.			DWG NO. BO06				A4	
								REVISION	
WEIGHT: 9.3Gm			SCALE:1:1			SHEET 1 OF 1			