



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 <p>BEACON OPTRONICS The Shape of Light</p>				<p>Plastic Moulding General Tolerances if not otherwise shown: According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</p>		<p>DO NOT SCALE DRAWING</p>		<p>FIRST ANGLE PROJECTION</p> 	
						<p>BEACON OPTRONICS</p>			
	NAME	SIGNATURE	DATE	<p>Family</p> <p>Blaze Series</p> <p>PRT NO. BO08-Blaze-24x1-2835/3030-60°</p>					
DRAWN	Ankur Sharma	Ankur Sharma	21.02.2023						
CHK'D	Anuj Sharma	Anuj Sharma	21.02.2023						
APPV'D	Pradyumna Shandilya	Pradyumna	21.02.2023						
MATERIAL:		Polycarbonate(Makrolon 2407,Teijin 1225Z)		<p>DWG NO. BO08</p> <p>A4</p>					
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2		This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.							
WEIGHT: 7.0Gm				SCALE:1:1			SHEET 1 OF 1		REVISION 00