



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTRONICS The Shape of light</div>			<div>Plastic Mounting General Tolerances if not otherwise shown: According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C. According to DIN ISO 2768-2 Form and position: class L</div>			<div>DO NOT SCALE DRAWING</div>		<div>FIRST ANGLE PROJECTION</div> <div></div>					
						BEACON OPTRONICS							
		NAME		SIGNATURE		DATE		<div>Family</div> <div>Custom Series</div> <div>PRT NO.</div> <div>BO107-Custom-9x1-5050-Type-IIS</div>					
DRAWN		Ankur Sharma		Ankur Sharma		29.07.2024							
CHK'D		Anuj Sharma		Anuj Sharma		29.07.2024							
APPV'D		Pradyumna Shandilya		Pradyumna		29.07.2024							
MATERIAL:		Polycarbonate(Makrolon 2407,Teijin 1225Z)											
<div>1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2</div>		<div>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</div>						DWG NO.		BO107		A4	
												REVISION:-0.0	
		WEIGHT: 16.0 Gm						SCALE:1:1		SHEET 1 OF 1			