



SECTION A-A

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of Light			Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L		DO NOT SCALE DRAWING		FIRST ANGLE PROJECTION						
BEACON OPTRONICS													
		NAME	SIGNATURE	DATE	Family								
DRAWN		Ankur Sharma	Ankur Sharma	04.09.2024	Sunbeam Series								
CHK'D		Anuj Sharma	Anuj Sharma	04.09.2024									
APPV'D		Pradyumna Shandilya	Pradyumna	04.09.2024	PRT NO.		BO117-Sunbeam-1x1-3535-3°						
MATERIAL:		Polycarbonate(Makrolon 2407,Teijin 1225Z)											
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2		This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.			DWG NO.		BO117			A4			
										REVISION-00			
		WEIGHT: 12.8 Gm			SCALE:2:1				SHEET 1 OF 1				