



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 <b>BEACON OPTONICS</b> The Shape of Light			Plastic Moulding General Tolerances if not otherwise shown: According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L		DO NOT SCALE DRAWING		FIRST ANGLE PROJECTION 			
					<b>BEACON OPTONICS</b>					
	NAME	SIGNATURE	DATE	Family <b>Glitter Series</b>						
DRAWN	Ankur Sharma	Ankur Sharma	03.11.2024							
CHK'D	Anuj Sharma	Anuj Sharma	03.11.2024							
APPV'D	Pradyumna Shandilya	Pradyumna	03.11.2024							
MATERIAL: <b>Polycarbonate(Makrolon 2407,Teljin 1225Z)</b>				PRT NO. <b>BO127-Glitter-2x2-5050-120x20°</b>						
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2										
This drawing is the property of Beacon Optonics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optonics.				DWG NO. <b>BO127</b>					A4	
WEIGHT: 12 Gm				SCALE:1:1					REVISION:00	
				SHEET 1 OF 1						