



Isometric View

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of Light			Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L			DO NOT SCALE DRAWING		FIRST ANGLE PROJECTION					
BEACON OPTRONICS													
	NAME		SIGNATURE		DATE		Family Blaze Series						
	DRAWN		Ankur Sharma		Ankur Sharma							03.11.2024	
	CHK'D		Anuj Sharma		Anuj Sharma		03.11.2024		PRT NO. BO129-Blaze-24x1-3030-T2				
	APPV'D		Pradyumna Shandilya		Pradyumna		03.11.2024						
MATERIAL:	Polycarbonate(Makrolon 2407,Teijin 1225Z)												
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.					DWG NO.			BO129			A4	
												REVISION-00	
	WEIGHT: 8.5Gm					SCALE:1:1			SHEET 1 OF 1				