



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 <b>BEACON OPTONICS</b> The Shape of Light			<p>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</p>		<p>DO NOT SCALE DRAWING</p>		<p>FIRST ANGLE PROJECTION</p> 		
					<b>BEACON OPTONICS</b>				
	NAME	SIGNATURE	DATE	<p>Family</p> <b>Jupiter Series</b>  PRT NO. <b>BO19-Jupiter-8x1-5050-30°</b>					
DRAWN	Ankur Sharma	Ankur Sharma	14.03.2023						
CHK'D	Anuj Sharma	Anuj Sharma	14.03.2023						
APP'VD	Pradyumna Shandilya	Pradyumna	14.03.2023						
MATERIAL:		Polycarbonate(Makrolon 2407,Teijin 1225Z)			<p>DWG NO. <b>BO19</b></p> <p>A4</p> <p>REVISION NO.</p>				
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2		This drawing is the property of Beacon Optonics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optonics.							
WEIGHT: 15.1Gm		SCALE:1:1			SHEET 1 OF 1				