



SCALE 3 : 1

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div><p>BEACON OPTRONICS The Shape of Light</p></div>			<p>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</p>		<p>DO NOT SCALE DRAWING</p>		<p>FIRST ANGLE PROJECTION</p> <div></div>	
<p>BEACON OPTRONICS</p>								
	NAME	SIGNATURE	DATE	<p>Family</p> <p>Sunbeam Series</p> <p>PRT NO.</p> <p>BO39-Sunbeam-1x1-2835/3030-45°</p>				
DRAWN	Ankur Sharma	Ankur Sharma	5.04.2023					
CHK'D	Anuj Sharma	Anuj Sharma	5.04.2023					
APP'VD	Pradyumna Shandilya	Pradyumna	5.04.2023					
MATERIAL:	Polycarbonate(Makrolon 2407,Teijin 1225Z)							
<p>1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2</p>	<p>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</p>			DWG NO.		A4		
				BO39		REVISION:00		
WEIGHT: 1.8Gm			SCALE:2:1		SHEET 1 OF 1			