



Side View

SECTION A-A

Isometric View

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTONICS</div> <div>The Shape of Light</div>			<div>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</div>			<div>DO NOT SCALE DRAWING</div>		<div>FIRST ANGLE PROJECTION</div> <div></div>			
						BEACON OPTONICS					
	NAME		SIGNATURE		DATE		Family				
DRAWN		Ankur Sharma		Ankur Sharma		5.04.2023		Glitter Series			
CHK'D		Anuj Sharma		Anuj Sharma		5.04.2023					
APPVD		Pradyumna Shandilya		Pradyumna		5.04.2023					
MATERIAL:		Polycarbonate(Makrolon 2407,Teijin 1225Z)				PRT NO.		BO41-Glitter-2x2-3535/5050-60°			
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2		This drawing is the property of Beacon Optonics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optonics.				DWG NO.		BO41		A4	
								REVISION:00			
		WEIGHT: 11.8Gm				SCALE:1:1		SHEET 1 OF 1			