



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of Light			Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L			DO NOT SCALE DRAWING		FIRST ANGLE PROJECTION 	
						BEACON OPTRONICS			
	NAME	SIGNATURE	DATE	Family					
DRAWN	Ankur Sharma	Ankur Sharma	5.04.2023	Glitter Series					
CHK'D	Anuj Sharma	Anuj Sharma	5.04.2023						
APP'D	Pradyumna Shandilya	Pradyumna	5.04.2023						
MATERIAL:	Polycarbonate(Makrolon 2407,Teijin 1225Z)			PRT NO.					
				BO56-Glitter-2x2-5050-20°					
1-All Dimensions are in mm 2-Open Tolerance is +/-0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.			DWG NO.					
				BO56					
				A4					
				REVISION:00					
WEIGHT: 16.2 Gm				SCALE:1:1			SHEET 1 OF 1		

	NAME	SIGNATURE	DATE
DRAWN	Ankur Sharma	Ankur Sharma	5.04.2023
CHK'D	Anuj Sharma	Anuj Sharma	5.04.2023
APP'VD	Pradyumna Shandilya	Pradyumna	5.04.2023

MATERIAL:	Polycarbonate(Makrolon 2407,Teijin 1225Z)
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.
	WEIGHT: 16.2 Gm