



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of Light			<p>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</p>		<p>DO NOT SCALE DRAWING</p>		<p>FIRST ANGLE PROJECTION</p> 				
					BEACON OPTRONICS						
	NAME		SIGNATURE		DATE		<p>Family</p> Jupiter Series				
DRAWN	Ankur Sharma		Ankur Sharma		5.04.2023						
CHK'D	Anuj Sharma		Anuj Sharma		5.04.2023						
APPV'D	Pradyumna Shandilya		Pradyumna		5.04.2023						
MATERIAL:		Polycarbonate(Makrolon 2407,Teijin 1225Z)				PRT NO.		BO60-Jupiter-8x1-5050-25°			
<p>1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2</p>		<p>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</p>				DWG NO.		BO60		A4	
										REVISION:00	
		WEIGHT: 13.7Gm				SCALE:1:1			SHEET 1 OF 1		