



Side View

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 <p>BEACON OPTRONICS The Shape of Light</p>				Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L		DO NOT SCALE DRAWING	FIRST ANGLE PROJECTION	
				BEACON OPTRONICS				
				Family Custom Series				
				PRT NO. BO65-Custom-52x1-2835/3030-60°				
				DWG NO. BO65				
				A4				
				REVISION:00				
				SHEET 1 OF 1				
				SCALE:1:1				
				WEIGHT: 21.5 Gm				

1:-All Dimensions are in mm
2:-Open Tolerance is +/- 0.2

This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.