



Isometric View

Side View

SECTION A-A
SCALE 1.5 : 1

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of Light			<p>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</p>		<p>DO NOT SCALE DRAWING</p>		<p>FIRST ANGLE PROJECTION</p> 		
					BEACON OPTRONICS				
	NAME	SIGNATURE	DATE	<p>Family</p> Sunbeam Series					
DRAWN	Ankur Sharma	Ankur Sharma	08.05.2024						
CHK'D	Anuj Sharma	Anuj Sharma	08.05.2024						
APPV'D	Pradyumna Shandilya	Pradyumna	08.05.2024						
MATERIAL:		Polycarbonate(Makrolon 2407,Teijin 1225Z)			<p>PRT NO.</p> BO79-Sunbeam-1x1-3535-7°				
<p>1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2</p>		<p>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</p>			<p>DWG NO.</p> BO79				A4
									REVISION:00
		WEIGHT: Lens 2.9 / Holder 1.8 Gm			SCALE:2:1		SHEET 1 OF 1		