



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div>			<div>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2</div> <div>Form and position: class L</div>			<div>DO NOT SCALE DRAWING</div>			<div>FIRST ANGLE PROJECTION</div> <div></div>								
						BEACON OPTRONICS											
	NAME		SIGNATURE		DATE												
DRAWN		RIJWAN		RIJWAN				Family				Aura Series					
CHKD		YASH		YASH													
APPVD		PRADYUMNA		PRADYUMNA				PRT NO.				BO137-Aura-5050-90D					
MATERIAL		Polycarbonate (Makrolon 2407 , Teijin 1225Z)															
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2		This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.					DWG NO.				BO137				A3		
															REVISION-00		
		WEIGHT:		135gm		SCALE 1:1				SHEET 1 OF 1							