



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div>			<div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2</div> <div>Form and position: class L</div>			<div>DO NOT SCALE DRAWING</div>			<div>FIRST ANGLE PROJECTION</div> <div></div>								
						BEACON OPTRONICS											
			NAME			SIGNATURE			DATE								
DRAWN			RIJWAN			RIJWAN			23-10-24								
CHKD			YASH			YASH			23-10-24								
APPVD			PRADYUMNA			PRADYUMNA			23-10-24								
MATERIAL			Polycarbonate (Makrolon 2407 , Teijin 1225Z)						PRT NO.								
<div>1--All Dimensions are in mm 2--Open Tolrance is +/- 0.2</div>			<div>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</div>						DWG NO.			A3					
									BO149						REVISION-00		
									SCALE 1:1			SHEET 1 OF 1					