



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div><div>BEACON OPTRONICS</div><div>The Shape of light</div></div>				<div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</div>		<div>DO NOT SCALE DRAWING</div>		<div>FIRST ANGLE PROJECTION</div> <div></div>	
<div>BEACON OPTRONICS</div>									
		NAME	SIGNATURE	DATE	Family				
DRAWN		RIJWAN	RIJWAN	07-11-24	Blaze Series				
CHKD		YASH	YASH	07-11-24					
APPVD		PRADYUMNA	PRADYUMNA	07-11-24					
MATERIAL		Polycarbonate (Makrolon 2407 , Teijin 1225Z)			PRT NO.				
<div>1--All Dimensions are in mm 2--Open Tolerance is +/- 0.2</div>		<div>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</div>			DWG NO.		A3		
					BO-8.1		REVISION-00		
		WEIGHT:			8gm	SCALE 1:1		SHEET 1 OF 1	