




Isometric View

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div><p>BEACON OPTRONICS The Shape of light</p></div>			<p>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</p>	<p>DO NOT SCALE DRAWING</p>		<p>FIRST ANGLE PROJECTION</p> <div></div>	
			<p>BEACON OPTRONICS</p>				
			<p>Family Sunbeam Series</p>				
			<p>PRT NO. BO146-Convex Lens</p>				
			<p>DWG NO. BO146</p>			<p>A3</p>	
			<p>SCALE 1:1</p>			<p>REVISION-00</p>	
			<p>SHEET 1 OF 1</p>				

	NAME	SIGNATURE	DATE
DRAWN	RIJWAN	RIJWAN	10-12-24
CHKD	YASH	YASH	10-12-24
APPVD	PRADYUMNA	PRADYUMNA	10-12-24
MATERIAL	Polycarbonate (Makrolon 2407 , Teijin 1225Z)		
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.		
WEIGHT:			

<div></div> <div>BEACON OPTRONICS The Shape of light</div>			Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L
	NAME	SIGNATURE	DATE
DRAWN	RIJWAN	RIJWAN	10-12-24
CHKD	YASH	YASH	10-12-24
APPVD	PRADYUMNA	PRADYUMNA	10-12-24
MATERIAL	Polycarbonate (Makrolon 2407 , Teijin 1225Z)		
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.		
	WEIGHT:		