



SECTION A-A

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

		<div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div>			<div>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</div>		<div>DO NOT SCALE DRAWING</div> <div>FIRST ANGLE PROJECTION</div>	
			NAME	SIGNATURE	DATE	<div>BEACON OPTRONICS</div> <div>Family</div> <div>SUNBEAM SERIES</div> <div>PRT NO.</div> <div>BO147-Sunbeam-1X1-3535 RGBW-25D</div> <div>DWG NO.</div> <div>BO147</div> <div>A3</div> <div>REVISION-00</div>		
		DRAWN	RIJWAN	RIJWAN	27-11-24			
		CHKD	YASH	YASH	27-11-24			
		APPVD	PRADYUMNA	PRADYUMNA	27-11-24			
7mm		MATERIAL	Polycarbonate (Makrolon 2407 , Teijin 1225Z)			<div>SCALE 1:1</div> <div>SHEET 1 OF 1</div>		
		1-:All Dimensions are in mm 2-:Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.					
			WEIGHT: 3.5gm					