



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div>			<div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2</div> <div>Form and position: class L</div>			<div>DO NOT SCALE DRAWING</div>			<div>FIRST ANGLE PROJECTION</div> <div></div>			
						<div>BEACON OPTRONICS</div>						
	NAME		SIGNATURE		DATE		<div>Family</div> <div>Sunbeam Series</div>					
DRAWN	RIJWAN		RIJWAN		10-12-24							
CHKD	YASH		YASH		10-12-24							
APPVD	PRADYUMNA		PRADYUMNA		10-12-24		<div>PRT NO.</div> <div>BO172-Sunbeam-1x1-3535-17*</div>					
MATERIAL	Polycarbonate (Makrolon 2407 , Teijin 1225Z)					<div>DWG NO.</div> <div>BO172</div>						
<div>1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2</div>	<div>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</div>											
	WEIGHT: 3.5gm					SCALE 1:1			SHEET 1 OF 1			
						<div>A3</div> <div>REVISION-00</div>						