



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

| | | | | | | | | | | | |
|--|--|--|---|--|--|--|--|--|--|-------------------------|--|
| <div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div> | | | <div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2</div> <div>Form and position: class L</div> | | | <div>DO NOT SCALE DRAWING</div> | | | <div>FIRST ANGLE PROJECTION</div> <div></div> | | |
| | | | | | | <div>BEACON OPTRONICS</div> | | | | | |
| | | | | | | <div>Family</div> <div>Sunbeam Series</div> | | | | | |
| <div>DRAWN</div> <div>RIJWAN</div> <div>RIJWAN</div> <div>05-03-25</div> | | | | | | <div>PRT NO.</div> <div>BO175-Sunbeam-1x1-5050-GEN-1-25°</div> | | | | | |
| <div>CHKD</div> <div>YASH</div> <div>YASH</div> <div>05-03-25</div> | | | | | | | | | | | |
| <div>APPVD</div> <div>PRADYUMNA</div> <div>PRADYUMNA</div> <div>05-03-25</div> | | | | | | | | | | | |
| <div>MATERIAL</div> <div>Polycarbonate (Makrolon 2407 , Teijin 1225Z)</div> | | | | | | | | | | | |
| <div>1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2</div> | | | | | | <div>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</div> | | | | | |
| <div>WEIGHT:</div> <div>3.5gm</div> | | | | | | <div>DWG NO.</div> <div>BO175</div> | | | | <div>A3</div> | |
| | | | | | | <div>SCALE 1:1</div> | | | | <div>SHEET 1 OF 1</div> | |
| | | | | | | <div>REVISION-00</div> | | | | | |