



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div>			<div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2</div> <div>Form and position: class L</div>			DO NOT SCALE DRAWING			FIRST ANGLE PROJECTION 					
BEACON OPTRONICS														
			Family Sunbeam Series											
DRAWN			RIJWAN		RIJWAN		10-11-24		PRT NO. BO202-Sunbeam-1x1-2835-3030-Asymmetric Deg					
CHKD			YASH		YASH		10-11-25							
APPVD			PRADYUMNA		PRADYUMNA		10-11-24							
MATERIAL			Polycarbonate (Makrolon 2407 , Teijin 1225Z)											
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2			This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.					DWG NO. BO201			A3			
WEIGHT:			3gm					SCALE 1:1			SHEET 1 OF 1		REVISION-00	