



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

| | | | | | | | | | | | | | |
|---|--|---|--|---|--|----------|--|-------------------------------------|--|--|--|-------------------------|--|
| 4,24 | <div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div> | | | <div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2</div> <div>Form and position: class L</div> | | | <div>DO NOT SCALE DRAWING</div> | | | <div>FIRST ANGLE PROJECTION</div> <div></div> | | | |
| | | | | | | | <div>BEACON OPTRONICS</div> | | | | | | |
| | | | | | | | <div>Family</div> <div>Theia Series</div> | | | | | | |
| | | | | | | | <div>PRT NO.</div> <div>BO227-Theia-28x1-5050-Typell</div> | | | | | | |
| DRAWN | | RIJWAN | | RIJWAN | | 08-04-25 | | <div>DWG NO.</div> <div>BO227</div> | | | | <div>A3</div> | |
| CHKD | | YASH | | YASH | | 08-04-25 | | | | | | REVISION-00 | |
| APPVD | | PRADYUMNA | | PRADYUMNA | | 08-04-25 | | | | | | | |
| MATERIAL | | Polycarbonate (Makrolon 2407 , Teijin 1225Z) | | | | | | <div>SCALE 1:1</div> | | | | <div>SHEET 1 OF 1</div> | |
| 1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2 | | This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics. | | | | | | | | | | | |
| WEIGHT: | | 63gm | | | | | | | | | | | |