



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div> BEACON OPTRONICS The Shape of light</div>			<div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</div>			<div>DO NOT SCALE DRAWING</div>			<div>FIRST ANGLE PROJECTION</div> <div></div>			
						BEACON OPTRONICS						
						Family Shimmer Series						
DRAWN			RIJWAN		RIJWAN		04-12-2024		PRT NO. BO25-Shimmer-16x1-2835/3030-TypeIV			
CHKD			YASH		YASH		04-12-2024					
APPVD			PRADYUMNA		PRADYUMNA		04-12-2024					
MATERIAL			Polycarbonate (Makrolon 2407 , Teijin 1225Z)									
1-All Dimensions are in mm 2-Open Tolerance is +/- 0.2			This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.					DWG NO. BO25			A3	
			WEIGHT: 09gm					SCALE 1:1			SHEET 1 OF 1	
											REVISION-00	