



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

<div></div> <div>BEACON OPTRONICS</div> <div>The Shape of light</div>			<div>Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</div>			<div>DO NOT SCALE DRAWING</div>		<div>FIRST ANGLE PROJECTION</div> <div></div>			
						<div>BEACON OPTRONICS</div>					
		NAME	SIGNATURE	DATE	<div>Family</div> <div>Custom Series</div>						
DRAWN	RIJWAN	RIJWAN	06-02-25								
CHKD	YASH	YASH	06-02-25								
APPVD	PRADYUMNA	PRADYUMNA	06-02-25		<div>PRT NO.</div> <div>BO75.1-Custom-29x1-5050-Typell</div>						
MATERIAL	Polycarbonate (Makrolon 2407 , Teijin 1225Z)				<div>DWG NO.</div> <div>BO75</div>				<div>A3</div>		
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.								REVISION-00		
WEIGHT:	65gm								SCALE 1:1	SHEET 1 OF 1	