



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of light			Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L		DO NOT SCALE DRAWING		FIRST ANGLE PROJECTION 	
				BEACON OPTRONICS				
DRAWN		RIJWAN	SIGNATURE		RIJWAN	Family		
CHKD		YASH	SIGNATURE		YASH	Aura Series		
APPVD		PRADYUMNA	SIGNATURE		PRADYUMNA	PRT NO.		
MATERIAL		Polycarbonate (Makrolon 2407 , Teijin 1225Z)					BO134-Aura-5050-60°	
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2		This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.				DWG NO.		A3
		WEIGHT: 105gm				BO134		REVISION-00
				SCALE 1:1		SHEET 1 OF 1		