



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

| | | | | | |
|---|--|------------------|---|---|---|
|  <p>BEACON OPTRONICS The Shape of light</p> | | | <p>Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L</p> | <p>DO NOT SCALE DRAWING</p> | <p>FIRST ANGLE PROJECTION</p>  |
| | | | <p>BEACON OPTRONICS</p> | | |
| <p>DRAWN</p> | <p>RIJWAN</p> | <p>RIJWAN</p> | <p>DATE</p> <p>27-10-25</p> | <p>Family</p> <p style="text-align: center;">Glitter Series</p> | |
| <p>CHKD</p> | <p>YASH</p> | <p>YASH</p> | <p>DATE</p> <p>27-10-25</p> | <p>PRT NO.</p> <p style="text-align: center;">BO331-Glitter-2x2-5050-120x20°</p> | |
| <p>APPVD</p> | <p>PRADYUMNA</p> | <p>PRADYUMNA</p> | <p>DATE</p> <p>27-10-25</p> | <p>DWG NO.</p> <p style="text-align: center;">BO331</p> | |
| <p>MATERIAL</p> | <p>Polycarbonate (Makrolon 2407 , Teijin 1225Z)</p> | | | <p>SCALE 1:1</p> | |
| <p>1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2</p> | <p>This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.</p> | | | <p>SHEET 1 OF 1</p> | |
| <p>WEIGHT: 17gm</p> | | | <p>REVISION-00</p> | | <p>A3</p> |