



- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of light			Plastic Moulding General Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L	DO NOT SCALE DRAWING	FIRST ANGLE PROJECTION 
			BEACON OPTRONICS		
			Glitter Series		
			PRT NO. BO336-Glitter-2x2-5050-15°		
			DWG NO. BO336		
			SCALE 1:1		
			SHEET 1 OF 1		
			A3		
			REVISION-00		
			WEIGHT: 22gm		

	NAME	SIGNATURE	DATE
DRAWN	RIJWAN	RIJWAN	28-10-25
CHKD	YASH	YASH	28-10-25
APPVD	PRADYUMNA	PRADYUMNA	28-10-25
MATERIAL	Polycarbonate (Makrolon 2407 , Teijin 1225Z)		
1:-All Dimensions are in mm 2:-Open Tolerance is +/- 0.2	This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.		