








SECTION C-C




A

A



SECTION A-A

- Lens Material : Polycarbonate(Makrolon 2407&2647/Teijin 1225Z)
- Operating Temperature : PC: -40°C~+110°C(Upper Limit +120°C)
- UL Flammability : PC 2407/1225Z: V-2 @0.75mm & HB @2.7mm
- UL RTI Elec : PC 2407/1225Z: 125°C @1.5mm
- Light Transmission Rate 400nm~900nm > 90%

 BEACON OPTRONICS The Shape of light			Plastic Moulding Genral Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: up to 30mm class M, otherwise class C According to DIN ISO 2768-2 Form and position: class L			DO NOT SCALE DRAWING		FIRST ANGLE PROJECTION 			
						BEACON OPTRONICS					
						Family Glitter Series					
DRAWN AMIR AMIR 23-03-26						PRT NO. BO381-Glitter-2x2-5050-Type-IV S					
CHKD YASH YASH 23-03-26											
APPVD PRADYUMNA PRADYUMNA 23-03-26											
MATERIAL Polycarbonate (Makrolon 2407 , Teijin 1225Z)						DWG NO. BO381			A3		
1-All Dimensions are in mm 2-Open Tolerance is +/- 0.2 This drawing is the property of Beacon Optronics. It may not be reproduced, copied or communicated without a written agreement with Beacon Optronics.									REVISION-00		
WEIGHT: 7 gm						SCALE 1:1		SHEET 1 OF 1			